



## Lifetime No Leak Guarantee On RV FlexArmor<sup>®</sup> Roof

**LIFETIME GUARANTEE-** We warrant the RV FlexArmor<sup>®</sup> roof application (“application”) to be, at time of application, free from defects in material and workmanship under normal use and service, and we or another Certified Service Center, will, during the lifetime of the RV, repair any effected areas. The lifetime warranty covers against leaks around fixtures as they were when the roof was applied. Any additions are not covered under said warranty unless brought back to a Service Center for resealing.

Any needed repair or replacement of parts under the terms of this warranty should be brought to our attention or to any other convenient Service Center listed on our website, RVRoof.com. Notice of a defect to these persons will constitute notice to Corporate. In the event that no Service Center exists in your area, you should notify RVRoof.com, Inc. at :

Mail: RVRoof.com, Inc., 1580 Rivers Road, Green Cove Springs, FL 32043

Email: Sales@RVRoof.com

This warranty shall NOT apply under the following conditions:

1. When the roof has been purposely modified to install a device to the roof that requires cutting or drilling into the roof and you have failed to have the area resealed by an authorized Service Center within one year.
2. When the roof has been damaged by an accident, such as motor vehicle incident and you have failed to have the area resealed by an authorized Service Center within one year.
3. When the roof is serviced by unauthorized persons.
4. Failure of coax rubber boots on TV antennae. Boot must be inspected and replaced if deteriorated.
5. A/C gasket failure. A/C gaskets need to be inspected and replaced when needed.
6. Cracked skylights above coating line.

This warranty is given by RVRoof.com, Inc., 1580 Rivers Road, Green Cove Springs, FL 32043. The warranty gives you specific legal rights and you may also have other rights which vary from state to state. Owner must provide original receipt and warranty for all claims.

### Use and Care of Roof:

Wash with non abrasive household cleaners. Mild bleach/water solutions are acceptable.

Maintain white top coat. The original topcoat should last 10-15 years dependent on conditions. Once grey starts to show through white topcoat, it needs to be reapplied. Contact nearest Service Center for appointment or to have topcoat shipped for self application.

Owner should inspect seals and edges of roof periodically.